ASTORkork 15506/1

Cork-Distance Pads with Adhesive Foam





ASTORkork 15506/1

Cork distance pads with adhesive foam, multi-row on roll, for storing and transportation of glass or other surfaces with need of protection, e.g. plastics, metals coated surfaces.

Properties and Applications

- For use as distance pads in the glass industry
- Can also be used on plastics, metals and coated surfaces (pre-tests are recommended)
- Absorbs vibration and shock and prevents slip for optimal safety in transportation
- High compression hardness, i.e. takes high load
- With self-adhesive foam for residual free removal
- Supplied as roll of 162 mm width, multi-row die-cut
- Cork thickness: standard 2 and 3 mm (plus 2.5 mm PVC-foam), up to 6 mm possible

Technical Data - Cork

Cork hard press-cork

Standard thickness 2 - 6 mm (up to 25 mm possible)

Density ca. 200 kg/m³

Shore hardness A 50

Tensile strength $6-8 \text{ kg/cm}^2$

Compression set < 25%

Heat conduction factor λ 0.040 W/m $^{\circ}$ C

Technical Data - Adhesive Foam

Foam mixed-cell PVC Foam

Density ca. 100 – 125 kg/m3

Tensile strength DIN 53571 > 100 KPa
Elongation at break DIN 53571 > 120 %
Colour white

Thickness 2 - 2.5 mm

All data are single values and are not to be considered as specifications We recommend to perform own tests to ensure suitability.