

ASTORKork 15509

Cork/foam spools for Lisec applicator



ASTORKork 15509

Spools (bobbin) made of combi-cork (cork with adhesive foam) for use in Lisec applicator. The cork band is without die-cut and has no liner.

In the Lisec applicator it is applied (cut and placed) on glass, i.e. as distance pad for storing and transportation of glass or other surfaces with need of protection, e.g. plastics, metals coated surfaces.

Properties and Applications

- Spools without liner and die-cut
- For use as distance pads in the glass industry, i.e. Lisec Applicator
- Can also be used on plastics, metals and coated surfaces (pre-tests are recommended)
- Absorbs vibration and shock and prevents slip for optimal safety in transportation
- High compression hardness, i.e. takes high load
- With self-adhesive foam for residual free removal
- Dimensions: length 300 meters, width 18 mm
- Flanch: plastic ring with inner diameter of 73 mm

Technical Data Cork

Cork	hard press-cork
Standard thickness	2.8 mm
Density	ca. 200 kg/m ³
Shore hardness A	50
Tensile strength	6 – 8 kg/cm ²
Compression set	< 25%
Heat conduction factor λ	0.040 W/m °C

Technical Data Adhesive Foam

Foam	mixed-cell PVC Foam
Density	ca. 100 – 125 kg/m ³
Tensile strength DIN 53571	> 100 KPa
Elongation at break DIN 53571	> 120 %
Colour	white
Thickness	2 - 2.5 mm

All data are single values and are not to be considered as specifications We recommend to perform own tests to ensure suitability